




LED Interactive Touch Screen



Product Introduction

HOLKOI-01N LED Interactive Touch Screen is an intelligent writing panel With a triple-sided ultra-narrow bezel design, sliding door lock protection and 4K UHD display, it's equipped with interactive whiteboards and wireless screen casting software in a man-machine Interaction way, enabling an interactive mode with multiple users and inter-connectivity, enriching presentation and enhancing the communication atmosphere.

Quotation

Items	Product & Model	Main Configurations		
1	 LED Interactive touch screen 01N-65LED	65" or 75" or 86"ED Interactive Panel <ul style="list-style-type: none">* 20 points touch* 4K UHD resolution* Panel OS: Android 9.0, 4G RAM, 32G ROM* OPS : I5th, 8G, 128G, Pre-install Win10		

1.

Applications



Specifications

Panel Parameters

LED Panel Size	65",75" and 86" or (1655 mm, 1906 mm, 2185 mm)
Backlight Type	LED (DLED)
Resolution(H×V)	3840×2160 (UHD)
Color	10 bit 1.07B
Brightness	550cd/m ²
Contrast	4000:1 (according to panel brand)
Viewing angle	178°
Display protection	4 mm tempered explosion-proof glass
Backlight lifetime	50000 hours
Speakers	15W*2 / 8Ω

System Parameters

Operating System	Android System	Android 9.0
	CPU (Processor)	Quad Core 1.5GHz
	Storage	RAM 4G; ROM 32GB
	Network	LAN/ WiFi 2.4G +5G
Windows System (OPS)	CPU	i5 or i3 or ii7 optional)
	Storage	Memory: 8G (4G/16G optional) ; Hard Disk: 128G SSD (256G/512G/1TB optional)
	Network	LAN/ WiFi
	OS	Pre-install Windows 10 Pro

Camera and Microphone Parameters (Optional)

Camera	Pixel: 8.0 M Video resolution: 3840*2160 Lens: Fixed focal length lens, effective focal length 4.11mm Drive: Free drive
Microphone	Microphone type: Digital array microphone Number of digital marks: 6 Pickup distance: 10 m Drive: Windows 10 free drive Echo cancellation: Supported

Touch Parameters

Touch technology	IR touch; 20 points; HIB Free drive
Response speed	≤ 8ms
Operation system	Support Windows7/10, Android, Mac OS, Linux
Working temperature	0℃~60℃
Operating Voltage	DC5V
Power consumption	≥0.5W

Electrical Performance

Max Power	≤250W	≤300W	≤400W
Standby power	≤0.5W		
Voltage	110-240V(AC) 50/60Hz		

Connection Parameters and Accessories

Input ports	AV*1, YPbPR*1, VGA*1, AUDIO*1, HDMI*3(Front*1), LAN(RJ45) *1
Output Ports	SPDIF*1, Earphone*1
Other Ports	USB2.0*2, USB3.0*3 (front*3) , RS232*1, Touch USB*2(front*1)
Function buttons	7 buttons in front bottom frame: Power, Source, Volume+/-, Home, PC, Eco
Accessories	Power cable*1; Remote Control*1; Touch Pen*1; Instruction manual*1; Warranty card*1; Wall brackets*1 set

Product Dimension

Items / Model No.	01N-65LED	01N-75LED	01N-86 LED
Panel Size	65"	75"	86"
Product dimension	1490*906*95mm	1710*1030*95mm	1957*1170*95mm
Packing dimension	1620*1054*200mm	1845*1190*200mm	2110*1375*200mm
Wall mount VESA	500*400mm	600*400mm	750*400mm
Weight	41kg/52kg	56 kg/67 kg	71 kg/82 kg